



# CONSTRUCTION WORK

**MODEL:  
A2ACT**

## TECHNICAL SPECIFICATIONS

### Features

Fall arrest and work positioning harness. Features integral padded shoulders and waist support positioning pads. Dorsal "D" ring as fall arrest element and two hip "D" rings as positioning elements. Pass through buckles at chest and tongue buckles for leg adjustment.

### Materials

1 ¾" polyester webbing  
Stamped steel ironwork  
100% polyester thread

### Performance Specification

**Webbing tension:**

6,800lbs

**Ring tension:**

5,000lbs

**Buckle tension:**

4,000lbs

**Harness freefall:**

100kgs (height varies)

**Ironwork corrosion:**

48 hours of saline exposure



### Compliant With

**System**

Fall Arrest  
Work Positioning

ANSI Z359.11-2014

EN 361:2002

NRF-024-PEMEX 2009

**Length**

A2ACT-S BX  
A2ACT-M/L BX  
A2ACT-XL/XXL BX

**Appliance**

General Industry  
Construction  
Public Services

**Weight**

2.22 kg S  
2.4 kg M/L  
2.58 kg XL/XXL



FM687317



icontec  
ANSLASSE Z359.11(2014)  
UNE-EN 361(2002)  
CSC-CER624347  
CSC-CER624355  
A2ACT ARNÉS DE POSICIONAMIENTO



Producto Probado

ISO/IEC 17025:2005  
N° MM-0354-040/12  
Laboratorio acreditado por EMA

Producto Certificado  
Escanea y descarga

