



**BASIC**

**MODEL :  
C11PAC**

**TECHNICAL SPECIFICATIONS**

**Features**

Adjustable double-leg energy absorbing lanyard. It features 1" polyester webbing and steel snap hooks for harness attachment and for anchorage connection.

**Materials**

1" Polyester webbing  
 Stamped steel ironwork  
 Tear web shock absorber  
 100% Polyester thread

**Performance Specification**

**Webbing :**  
 tension: 8,500lbs (37.8kN)

**Hook's :**  
 tension: 5,000lbs (22.2kN)  
 lateral load: 3,600lbs (16kN)  
 frontal load: 3,600lbs (16kN)

**Lanyard's freefall :**  
 tension: 128kgs at 1.80m. height

**Ironwork corrosion :**  
 48 hours of saline exposure



**Compliant With**

ANSI Z359.13-2013  
 ANSI Z359.1-2007  
 NRF-024-PEMEX 2009  
 ANSI A10.32-2012

**System** | Fall Arrest

**Length** | Adjustable  
 1.30m - 1.80m

**Appliance** | General Industry  
 Construction

**Weight** | 1.67 kg

Certified product  
 Scan and download



Tested product  
 ISO/IEC 17025:2005  
 N° MM-0354-040/12  
 Laboratorio acreditado por EMA