



**BASIC**

**MODEL :  
C1PGAC**

**TECHNICAL SPECIFICATIONS**

**Features**

6ft Adjustable single-leg energy absorbing lanyard. It features 1" polyester webbing, steel snap hooks for harness attachment and a single steel rebar hook for anchorage connection.

**Materials**

1" Polyester webbing  
Stamped steel ironwork  
Tear web shock absorber  
100% Polyester thread

**Performance**

**Specification**

**Webbing :**  
8,500lbs (37.8kN)

**Hook's :**  
tension: 5,000lbs (22.2kN)  
lateral load: 3,600lbs (16kN)  
frontal load: 3,600lbs (16kN)

**Lanyard's freefall :**  
tension: 128kgs at 1.80m. height

**Ironwork corrosion :**  
48 hours of saline exposure



**Compliant With**

ANSI Z359.13-2013  
ANSI Z359.1-2007  
NRF-024-PEMEX 2009  
ANSI A10.32-2012

**System**

Fall Arrest

**Length**

Adjustable  
(1.30m - 1.80m)

**Appliance**

General Industry  
Construction

**Weight**

1.50 kg



Tested product  
ISO/IEC 17025:2005  
N° MM-0354-040/12  
Laboratorio acreditado por EMA

Certified product  
Scan and download

