



**BASIC**

**MODEL :  
C1PRC**

**TECHNICAL SPECIFICATIONS**

**Features**

6ft Single-leg energy absorbing lanyard. It features 1" polyester webbing, steel snap hooks for harness attachment and anchorage connection. It also includes a tie-back "D" ring for wrap-around anchoring and eliminates the need for a separate anchorage connector.

**Materials**

1" Polyester webbing  
Stamped steel ironwork  
Tear web shock absorber  
100% Polyester thread

**Performance**

**Specification**

**Webbing :**  
tension: 5,000lbs (22.2kN)

**Hook's :**  
tension: 5,000lbs (22.2kN)  
lateral load: 3,600lbs (16kN)  
frontal load: 3,600lbs (16kN)

**Lanyard's freefall :**  
tension: 128kgs at 1.80m. height

**Lanyard :**  
3,600 (16kN)

**Ironwork corrosion :**  
48 hours of saline exposure



**Compliant With**

**System** | Fall Arrest

ANSI Z359.13-2013

**Length** | 6ft

**Appliance** | General Industry  
Construction

**Weight** | 1.23 kg



Tested product  
ISO/IEC 17025:2005  
N° MM-0354-040/12  
Laboratorio acreditado por EMA

Certified product  
Scan and download

